



REGULATIONS AND SPECIFICATIONS FOR THE 2015 NORTHERN REGIONS MOTORSPORT VW CHALLENGE CHAMPIONSHIP

MSA NORTHERN REGIONS MOTORSPORT CIRCULAR NR 15/2015 (159633/144)

1. VALIDITY OF THESE REGULATIONS

These regulations apply for the calendar year of 2015. The championship is held under MSA's general competition rules, standing supplementary regulations for car circuit racing, as well as these regulations.

Although care was taken to cover all possible modification and allowances, "grey" areas might still appear. The VW Challenge Technical Committee reserves the right to allow or not allow such modifications not covered.

2. DEFINITION

"VW Challenge" - A class of racing that complies with the following regulations:

2.1. Aim of the Championship

To declare an overall Northern Regions Motorsport "VW Challenge" Champion and a Northern Regions Champion in each class.

2.2. Controllers of the Championship

The Controllers of the 2015 "VW Challenge" Championship will be the MSA Northern Regions Motorsport Committee, together with the "VW Challenge" branch of the Sports Car Club of South Africa.

2.3. Practice/Testing

No 'away race' circuit may be used or hired for practice/testing, by either the competitor or their vehicle, from midnight on the Saturday one week prior to a scheduled championship race meeting at the particular circuit, until the start of official practice as detailed in the SR's for the event in question (an 'away race' is deemed to be one held at Phakisa, Lichtenburg, East London, Aldo Scribante or Killarney).

2.4. Spare or 'T' cars

No spare or 'T' cars are allowed. The car used by the competitor in his/her first official practice at a race meeting is the car nominated by the competitor to be used for the rest of the event in question.

2.5. Grid

Grid positions for Race 1 will be determined according to the fastest lap times posted during the official qualifying session. The starting positions for Race 2 shall be determined by the fastest lap time in the first heat. Non-qualifiers will start from the back of their class on the grid. Should there be more than one non qualifier, their grid positions will be determined by the current championship points standing of the competitor. Classes will be separated on the starting grid by two rows for all races or as decided by the CoC. Qualifying will be as per instructions of the SR's of the day.

2.6. Championship Scoring

2.6.1. Points will be awarded on 10-8-6-5-4-3-2-1 basis. In order for any competitor to score full points there must be at least eight (8) starters per class. Should a class not have eight (8) starters points will be awarded on a sliding scale, dropping the highest points scoring positions. The minimum number of starters required per class in order to score points is three (3).

2.6.2. To be classified as a starter a competitor must participate in any official timed practice session, or in at least one of the two races (heats) listed in the regulations for the event.

2.6.3. Pole position in each class will score one (1) additional point per class for the first race (heat) only.

2.6.4. Fastest race lap of each race (heat) will score one (1) additional point per class.

2.6.5. Class points may not be transferred from one class to another.

2.6.6. The champion will be the competitor with the highest number of points scored overall at the end of the racing season, irrespective of class.

2.6.7. Any competitor who, for the first time, joins any class in one of the last three events of the series will be excluded in the scoring towards championship points.

- 2.6.8. In the case of ties, these will be resolved in favour of the competitor with the greater number of wins, then second places and so on.
- 2.6.9. Competitors may not race in more than one Class during any given event.
- 2.6.10. Each competitor's best eight (8) race meeting results, out of the scheduled races of the 2014 calendar, shall count for the purpose of determining the final championship outcome.
- 2.7. Eligibility of Competitors
The championship is open to all paid up members of the "VW Challenge" branch of the Sports Car Club of South Africa who are holders of a valid MSA regional competition license.
- 2.8. Championship Race Dates
The race dates counting towards the championship will be as published and/or as amended by Motorsport South Africa.

3. **COMPETITORS CODE OF CONDUCT (REFER GCR 154).**

- 3.1. Competitors will abide by MSA regulations at all times. No competitor shall drive or conduct himself in a manner that brings the sport and/or club into disrepute. Competitors remain subject to disciplinary action imposed by MSA and/or the VW Challenge Committee. The competitor will be granted the opportunity to defend their case to the committee.
- 3.2. Dangerous or unsafe driving is not acceptable. Bumping and/or pushing of other vehicles on the circuit is not allowed and any drivers found doing this will be penalised by the Clerk of the Course in terms of GCR 157. The Clerk of the Course must consider infringements at previous events which resulted in penalties being imposed, when imposing penalties under this heading.
- 3.3. Any competitor who disadvantages another competitor by bumping said competitor's vehicle, even unintentionally which results in the loss of place(s) during a race will, at the discretion of the Clerk of the Course, generally be penalised so as to finish behind the competitor that was disadvantaged. More severe penalties will be applied in the case of repeat offenders.
- 3.4. The vehicle ahead of any other vehicle in any 'train' of two or more vehicles on the circuit may only change direction once in a straight line from the exit of one corner up to and including the entrance to the next corner unless involved in a genuine overtaking manoeuvre.
- 3.5. When attempting an overtaking manoeuvre coming into a turn, at the end of the braking area, the front bumper of the overtaking vehicle must be past the "B" pillar of the vehicle ahead before the entry to the turn.
 - 3.5.1. If this is not the case then the overtaking vehicle must back off and allow the vehicle ahead to take the racing line through the corner.
 - 3.5.2. If the bumper of the overtaking vehicle is past the "B" pillar of the vehicle ahead, the lead vehicle must take a line so as to allow both vehicles to successfully negotiate the corner and exit.

Note: This rule does not apply to 'sweeps', which are treated as normal 'straight line' racing.
- 3.6. It is highly recommended that all competitors have at least a forward facing video camera. This video material is to be made available to race officials in the case of incidents. Video material made available to race officials must be on a disk or suitable solid state media device in format usable on a Windows laptop. No video material will be considered if presented via the video camera's built in viewing screen.
- 3.7. Review of Incidents. In the event of conflicting incident reports from competitors and/or marshals and no suitable video material being available on the day, the CoC reserves the right to hold over any decision/sanction until a later date or the following race meeting, or when video evidence (if any) can be obtained. The onus is on the competitor to obtain and make available any video material to support their case. Every competitor is obliged to remain at the circuit for at least one hour after the publishing of the final race results. If a competitor does not make him/herself available when required by the CoC, a decision will be made without consideration of circumstances in incidents relating to that competitor.
- 3.8. Yellow/Red Cards will be issued by the CoC on recommendation from VW Challenge Disciplinary Committee.
- 3.9. VW Challenge Committee to ensure that a representative of the disciplinary committee is available to the CoC on Race days.
- 3.10. The VW Challenge Disciplinary Committee can temporarily withdraw the membership of any competitor.
- 3.11. If yellow card competitors cause an incident during the following three (3) race meetings, the CoC will issue a RED card and an immediate one race meeting ban.
- 3.12. When a competitor returns after a one race meeting ban, the yellow card will be applicable for a further 3 race meetings following the ban.

- 3.13. Yellow cards are to be displayed on the front and rear windows next to the competitor's number and next to the competitor's name on the side windows.
 - 3.14. Competitors racing under a yellow card will carry a 20 kg penalty over and above the usual weight for the class.
- 4. SPONSORS DECALS / COMPETITION NUMBER EXPOSURE.**
- 4.1. Refer to GCRs 246 and 249.
 - 4.2. Series sponsors decals must, on the onus of the competitor, be displayed at all times and must take preference over individual/ personal sponsors. The layout of sticker placement is shown on the VW Challenge website www.vwchallenge.co.za.
 - 4.3. Decals may not be tampered with or altered in any way.
 - 4.4. Day or series sponsors decals will be displayed where so decided and indicated by the VW Challenge Committee.
 - 4.5. The applicable areas are the bonnet, the top and bottom of the windscreen, the top and bottom of the back window, the front and back number plate, the number backings on both front doors and rear passenger windows.
 - 4.6. The VW Challenge Committee reserves the right to revise the abovementioned and/or add additional areas for the series sponsors of the VW Challenge. Numbers must be displayed on the windscreen.
 - 4.7. The letters designating the class must be the Committee-specified size. Only series sponsor decals and branding is allowed on the front windscreen, together with the competitor's class and number.
 - 4.8. Any competitor not running the correct stickers in the correct positions will, be penalised or excluded from the race/s.
- 5. ELIGIBILITY OF CARS**
- 5.1. Only right-hand drive VW passenger body shell types (front wheel drive, sedan or hatchback) based on those sold officially through VW dealers in South Africa, will be allowed.
 - 5.2. Cars must be registered with the Volkswagen Challenge Technical Committee, and be submitted for inspection to determine their eligibility.
 - 5.3. Cars not meeting the safety and aesthetic standards judged by the Volkswagen Challenge Committee will not be allowed to race.
 - 5.4. The VW Challenge Committee reserves the right to have racing cars inspected at random.
- 6. GENERAL**
- 6.1. Only modifications and allowances detailed herein are allowed.
 - 6.2. What is not specifically mentioned as allowed is expressly forbidden.
 - 6.3. All components not referred to or specifically mentioned in these regulations will remain in completely standard specification.
 - 6.4. Ignorance of the Regulations will not be accepted as an excuse.
 - 6.5. If there is any uncertainty as to the legality of the modification it is the responsibility of the competitor to seek clarification in writing from the VW Challenge technical committee. This must be done before the vehicle in question is entered in a race.
 - 6.6. All novice competitors must have completed drivers' instruction prior to the first race. The committee's decision is final as to whether or not the competitor is allowed to race.
 - 6.7. Any novice will race three consecutive race meetings with a red streamer affixed to the top of the rear window.
- 7. ADDITIONS AND AMENDMENTS**
- Any provision unforeseen in drawing up these regulations and specifications, or any additions or amendments to be made thereto, shall be the subject of an appendix to this circular to be issued by MSA which will have the same authority and effect as if it were part of these regulations and specifications.
- 8. DECLARATION OF CHAMPION**
- The MSA Northern Regions Motorsport Committee will, at its sole discretion, declare the winners of the championship. It is entitled to withhold such declaration if deemed necessary.

9. DATA LOGGING AND TELEMETRY

- 9.1. Data logging of car and competitor performance is allowed in all classes.
- 9.2. Telemetry: Any communication, whether this be data and/or voice between the car / driver and the pit whilst driving on the track, is not allowed.

10. CLASSES

There will be three classes, namely:

- 10.1. Class A: VW 16v 2.0L FSi
- 10.2. Class B: VW 8v, 2.0L engines with limited modifications.
- 10.3. Class C: VW 8v, 'Long-Block' 2.0L engines with limited modifications.

11. ENGINES (GENERAL)

Engine specifications and general measurements are available from the Technical Committee. All specifications are subject to 0.5 % tolerance except where no tolerance is allowed.

- 11.1. Oil coolers are free of restriction.
- 11.2. Spark plugs are free of restriction.
- 11.3. Gaskets are free of restriction.
- 11.4. The breather system must discharge into a catch tank of 1 litre minimum capacity, and this must be empty at the start of practice and each heat.
- 11.5. Sumps may be baffled but remain wet sumps. Engine and gearbox sump plugs and oil filters must be wire locked.
- 11.6. The position of the radiator may not be changed and remain as per standard OE with regards to vertical and horizontal positioning. Larger radiators may be fitted.
- 11.7. Alternators must be operative at all times, but all pulleys sizes may be changed.
- 11.8. Engine mounting position must remain standard, but the material is free. New Polo's must use original or VW Motorsport type engine mountings. For new models (Golf4/5 and Beetle) 2 out of 3 engine mountings must remain original. (Engine mounting on the driver side/engine side can be manufactured).
- 11.9. Service items such as filters, gaskets, lubricants, air, fuel and oil filters, bolts, fasteners and bearings may be sourced from any recognised aftermarket supplier of standard replacement parts.
- 11.10. Ducts may be added to increase airflow through radiator but must be fitted without protruding from the grill or any other part of the exterior of the car.

12. CYLINDER BLOCKS

- 12.1. Only VW mass-produced blocks available through commercial outlets are allowed. No aluminium blocks may be used in class B or class C.
- 12.2. Engine blocks which may have been damaged may be re-sleeved to return them to the original specifications.

13. BODYWORK AND GENERAL

- 13.1. No built out panels are allowed, but fender lips may be rolled or fenders flared to accommodate larger tyres specified.
- 13.2. Front valance may be cut to achieve better airflow to radiators only.
- 13.3. Outside shell appearance for all cars must appear original as per Volkswagen SA.
- 13.4. Paint colours may be changed and sticker patterns applied.
- 13.5. Body parts e.g. doors, boot, bonnets, bumpers must remain visually original externally but may have the insides lightened.
- 13.6. The front and rear spoiler is allowed to be of a type that is mass produced and must be similar in all regards to the standard OE SA spec spoiler for that specific vehicle. Front spoiler allowed for Mk1 Golf part no: Auto Style VW 01FS 002 or copy.
- 13.7. Splitters, aerofoils or aerodynamic devices designed to improve down force are not allowed.
- 13.8. Taping up or filling gaps in bonnets, doors etc. to aid aerodynamics are not allowed.
- 13.9. Headlights and tail lights must remain and be operable. The inner lights may be removed, but must be covered (with solid covers or wire mesh) as approved by the Technical Committee. Brake lights and rear indicators must be fully functioning.
- 13.10. Racing seat and steering wheel are free of restriction but must be securely fitted and technically approved.
- 13.11. Steering column may be lowered and extended but must be technically approved.

- 13.12. Pedals must remain in original position with a maximum additional extension of 10mm towards the driver by fitting a plate or rubber covering on top of the pedals. No further method of extending this reach to the pedals is allowed.
- 13.13. Full roll cages in compliance with GCR 239 are compulsory. The roll cage may protrude through the firewall and be connected to the front shock turrets. Roll cages must have at least six mounting points with at least one diagonal brace and a driver's door bar. A hole must be drilled in the main hoop to enable the scrutineers to check the pipe wall thickness.
- 13.14. The roll cage must include a safe method behind the driver's seat to stop the driver's seat from moving backwards in the case of an accident.
- 13.15. Heater boxes, interior trim and all passenger seats may be removed except for the dashboard, which shall remain standard apart from localised cutting for roll cages but may be an exact replica of the original and of any material.
- 13.16. Any form of instrument cluster may be used. Additional instruments may be fitted to measure engine performance.
- 13.17. Cut-off switches must be fully operational from inside and outside the car and shall be clearly marked.
- 13.18. Bonnet clips and safety nets must be fitted.
- 13.19. With the exception of windscreens all other glass may be substituted with Lexan with minimum thickness of 3 mm. They must be fitted in to the body with standard rubbers or pop rivets which may not be visible.
- 13.20. The battery must be positioned in the original position except in Class A and must be standard or must be rated at a least 30 Ah if not standard.
- 13.21. Transponders will be mounted on the roll cage between the rear side window and the roll cage behind the B-Pillar or on the rear side window itself.
- 13.22. Any form of electronic driver aid excluding data logging is strictly forbidden.
- 13.23. Soft towing straps or tow eyes that can hinge must be fitted to the front and rear of all cars. No metal part may protrude dangerously from the car when racing i.e. may not protrude in front of the bumper.

14. FUEL

- 14.1. Only standard 95 Octane petrol, freely available to the South African public, from dispensing pumps at commercial filling stations within the proximity of the race meeting, is allowed.
- 14.2. Octane booster, as approved by the Technical Committee, may be used at the coastal races.
- 14.2.1. The VW Challenge Committee and/or Technical Committee and/or VW Challenge Technical Consultant have the authority to nominate participants to use a control fuel as and when supplied. The Participant will be responsible for the payment of the fuel provided.

15. CLASS A 16V 2.0L

15.1. PISTONS AND RINGS

- 15.1.1. Only standard NA pistons may be used part number 06D 107 065 K or R or 06D 107 099 M
- 15.1.2. Oversize pistons are not allowed. 82.5mm standard
- 15.1.3. Minimum piston weight with rings and gudgeon pin is 390 grams.
- 15.1.4. Pistons may only be modified by removing metal on the underside of the piston for balancing purposes and on one plane to be machined for extra valve clearance to accommodate higher lift on camshaft. Sample piston is available from committee.



15.2. CONNECTING RODS

- 15.2.1. Only Standard OE VW FSi Conrods are to be used. Minimum weight is 510 grams.

15.2.2. Conrods may be balanced. One big end and one small end must remain standard.



15.3. **CRANKSHAFTS**

15.3.1. Stroking is not allowed.

15.3.2. May be balanced and reground.

15.3.3. Lightening is allowed by drilling and grinding.

15.3.4. Knife edging of webs is not allowed.

15.3.5. Side edging thickness of Web must remain standard (casting marks must remain visible).

15.3.6. Minimum weight of Crankshaft + Timing Wheel + Oil Pump gear is 15 Kg

15.3.7. Only cast steel crank may be used.

15.3.8. Only 2000cc crankshaft (92.8 mm stroke).



15.4. **FLYWHEEL AND CLUTCH**

15.4.1. Clutch plates are free of restriction.

15.4.2. May be lightened and balanced.

15.4.3. Min weight: Flywheel & pressure plate, excluding pressure plate to flywheel bolts: 7.5Kg.



15.5. **INDUCTION SYSTEMS**

15.5.1. Additional air pipes may be used to supply the engine air intake with cool air.

15.5.2. Air filters are free of restriction.

15.5.3. Throttle bodies and inlet manifold will be supplied by the association and may not be reworked.

15.5.4. An airbox as supplied by the association will be used.

- 15.5.5. The inlet port splitter must be removed.
- 15.5.6. 450mm collector undercut inlet manifold.

15.6. CYLINDER HEADS

- 15.6.1. Valves must remain standard as per OE specification and may not be modified in any way.
- 15.6.2. Only standard OE or exact replacement functional hydraulic followers may be used
- 15.6.3. FSi 16V hydraulic head.
- 15.6.4. Cylinder head must remain standard but only one chamber can be repaired.
- 15.6.5. Valve springs and retainers as per OE. All valve seats must remain standard 45 degree seat angles. Only the valve seat material i.e. not the cylinder head material may be machined.
- 15.6.6. Rocker/finger bearing pins may be welded to prevent separation.



15.7. COMPRESSION RATIO

- 11.2:1 maximum, No tolerance.

15.8. CAMSHAFTS

- 15.8.1. The rotary position of the camshaft to the crankshaft will be 105 crankshaft degrees at maximum lift.
- 15.8.2. Cam hydraulic duration will be measured with a Checking height of 0.07 mm.
- 15.8.3. Camshafts as supplied by VW Motorsport for Polo Cup or exact copies produced by van der Linde Developments. No Tolerance.
- 15.8.4. The rotary position of the camshaft to the crankshaft may be changed by using an adjustable vernier pulley in order to achieve 15.8.1. The same fixed cam timing will be used for all cars as determined by the technical committee.
- 15.8.5. Variable Valve Timing is not allowed.

15.9. GEARBOXES AND DIFFS

- 15.9.1. Only genuine VW 6-speed manual shift gearboxes may be used, as available on local models.
- 15.9.2. No automatic gearshift gearboxes in any form allowed.
- 15.9.3. No limited slip differentials.
- 15.9.4. Short shift gear linkage allowed.
- 15.9.5. Ratios must be VW OE replacement parts.
- 15.9.6. Linkage bushings may be changed for a harder material.
- 15.9.7. Drive shaft lengths may be modified to prevent C.V. joint failure.
- 15.9.8. Syncro rings may be removed
- 15.9.9. Only 6-speed Gearboxes with gear ratios with a tooth count of:

First Gear	3.7777	34 : 09
Second Gear	2.2666	34 : 15
Third Gear	1.6500	33 : 20
Fourth Gear	1.2692	33 : 26
Fifth Gear	1.0344	30 : 29
Sixth Gear	0.8648	32 : 37
Final Drive	3.9375	63 : 16

15.10. MANAGEMENT SYSTEMS

- Only Dicktator management, modified for a rev limiter at 7600rpm and certified as such by Dicktator, may be used.

15.11. IGNITION SYSTEMS

- 15.11.1. Must run Wasted Spark Coil Pack.

15.12. FUEL INJECTION

- 15.12.1. Any injector rail may be used.
- 15.12.2. Fuel pressure regulators are free of restriction.

- 15.12.3. More than one fuel pump is allowed.
- 15.12.4. Fuel pumps are free of restriction.
- 15.12.5. Exterior additional fuel surge tanks are allowed but must comply with the fuel regulations in the GCR's. The competitor must take full responsibility of the installation.
- 15.12.6. Fuel radiators/coolers or cooling of fuel in any way is not allowed.
- 15.12.7. Fuel injectors are free, but the original specification, part no. (Polo Cup) 06A 906 031 injectors are recommended.

15.13. **EXHAUST SYSTEMS**

- 15.13.1. Exhaust manifold lengths:



- 15.13.2. 1) 650mm, 2) 680mm, 3) 690mm, 4) 720mm
- 15.13.3. O.D. of primary pipes: 44.5mm
- 15.13.4. The collector must be a 4 into 1 and must exit with an OD of 54mm.
- 15.13.5. Must comply with GCR 245 and exhaust must exit at the rear of the car in the original position and direction.
- 15.13.6. The exhaust outlet pipe may not be recessed towards the inside of the bodywork of the vehicle, i.e. recessed further than the bottom part of the bodywork or bumper/spoiler where the exhaust protrudes.
- 15.13.7. The exhaust must also not protrude beyond the perimeter of the vehicle.
- 15.13.8. The exhaust may not be larger than 63mm OD and must follow the original route of the standard OE exhaust system.
- 15.13.9. Only one silencer box may be used and must be behind the rear axle.

15.14. **SUSPENSION**

- 15.14.1. Top shock turrets must remain in standard position except for modifications in terms of 15.14.18.
- 15.14.2. Standard VW OE steering rack and standard mounting positions only, power steering may be disconnected. If power steering is used it must be a standard VW part.
- 15.14.3. Bush material is free however must be dimensionally identical to standard items.
- 15.14.4. Pick-up points on body / chassis may not be changed or moved.
- 15.14.5. Steering knuckles must be a standard VW OE part and match the specific model of that vehicle.
- 15.14.6. Golf IV, P2 and P3 may use a rose joint in replacement of the rear control arm bush, but must be in the standard position.
- 15.14.7. Shocks / uprights may be slotted to achieve camber settings only.
- 15.14.8. Ball joints and their mountings may not be slotted. For camber purposes only, P2, P3, Golf 4, Golf 5, Golf 6 and Beetle may be fitted with ball joint adaptor plates allowing a maximum additional extension per side of 25mm. These adaptor plates may not be used to alter the lower control arm angle in any way. P2 Polos are allowed to use P3 control arms. The maximum track width must still be adhered to.
- 15.14.9. Top and bottom stress bars are allowed.
- 15.14.10. Droop may be limited.
- 15.14.11. Hubs of 4 or 5 stud type specification are allowed in all classes.
- 15.14.12. Camber/Caster plates with a maximum caster offset of 40 mm are allowed and may be fitted on top or directly below the turret.

- 15.14.13. Standard knuckle must be used without any alteration. Ackerman angle or bump-steer may not be altered.
- 15.14.14. Anti-roll bars and material are free. The roll bar may be fitted remotely in its working principle.
- 15.14.15. Rear axle may be stiffened by fitting fixed stiffeners.
- 15.14.16. Shock makes Bilstein, Koni, Gabriel, Monroe, Sachs, Wietec, Armstrong, Spax, Leda, Sax, KW or Traxion coil over type shocks are allowed.
- 15.14.17. Short rear shock absorbers may be accommodated by adding brackets to top and / or bottom mounting positions.
- 15.14.18. To accommodate long front absorbers front strut tower may be lengthened but 40mm castor offset must still be adhered to.
- 15.14.19. External gas canisters are allowed.
- 15.14.20. Spacer / mounting plate may be fitted between stub axle and rear axle assembly to allow for caliper to be shimmed with stub axle.
- 15.15. **BRAKES**
- 15.15.1. Boosters may be removed, but standard VW master cylinder must be retained.
- 15.15.2. Discs may be slotted and/or cross-drilled.
- 15.15.3. Rear brakes can be drums or discs.
- 15.15.4. Friction material is free.
- 15.15.5. Brake balance adjustment is allowed in car within reach of driver.
- 15.15.6. Any standard VW single piston floating caliper, aftermarket brake pads and discs up to a maximum of 288mm diameter allowed.
- 15.16. **WHEELS AND TYRES**
- 15.16.1. No chrome plated or split rims are allowed. Rim size 15 inch, 7J max.
- 15.16.2. Tyres are DUNLOP DZ03G H1 compound 195/55-R15, or as approved by the Technical Committee.
- 15.16.3. The VW Challenge Committee has the authority to appoint an official tyre marker at a race meeting.
- 15.16.4. At any given race meeting, four tyres will be positively identified by the technical committee or scrutineer prior to the start of qualifying or in the post-race paddock directly after qualifying and these tyres must be used for the remainder of the race meeting.
- 15.16.5. It is the responsibility of the competitor to ensure their tyres are marked.
- 15.16.6. It is the responsibility of the competitor to ensure that the tyre markings remain on the tyre, as the use of unmarked tyres during the meeting, inclusive of qualifying, can result in the exclusion of the competitor concerned.
- 15.16.7. The only time four new i.e. unmarked tyres may be used is at a competitor's first race of a new race season.
- 15.16.8. At the discretion of the technical consultant/scrutineer a damaged or defective tyre may be replaced during a race meeting with a tyre of similar wear.
- 15.16.9. In the event of a competitor replacing/building a new car they must transfer their current tyres to their new car.
- 15.16.10. Pressure controlling "pop-off" valves may not be used.
- 15.16.11. Two new tyres will be allowed every race meeting
- 15.17. **SPECIFICATION SHEET**
- Chassis specifications and general measurements are available from the Technical Committee. All specifications are subject to 0.5 % tolerance except where no tolerance is allowed. (P2 refers to 9N Polo and Vivo, P3 refers to new 6R Polo)
- 15.17.1. **Ground Clearance:**
- 120 mm minimum
 - Note: The measurements above are taken with the driver in the car from the centre of the bolt on the front inner lower control arm (standard mounting point) to the ground.
- 15.17.2. **Front Track Width:**
- This measurement will be taken at the bottom of the wheel (closest to the ground) from the outer edge of the wheel (rim) bead face.
 - The widest part of the opposing two wheel rims, no tolerance, 1740 mm for all models except Beetle (9C) which can be 1790mm.
- 15.17.3. **Wheel Base**

- The wheel base of a car may not be increased from the standard wheel base. Wheel base is measured from back of rear rim to back of front rim. The wheel base on the various models shall not exceed:
 - Golf Mk4 wheel base 2511mm (plus 5mm) maximum
 - Polo P2 (9N) wheel base 2460mm (plus 5mm) maximum
 - Polo P3 (6R) wheel base 2470mm (plus 5mm) maximum
 - Beetle wheel base 2508mm (plus 5mm) maximum
- Front control arms may not be pushed or spaced forward in any way. Sub frame may also not be slotted and standard diameter mounting bolts must be used.
- Rear axle mounting points may not be slotted or modified to allow wheel base to be lengthened or shortened.

15.18. CAR MASS (Including driver)

- 15.18.1. The vehicle mass is as car is raced. At no time of the event may a car weigh less than stipulated. No tolerance.
- 15.18.2. All cars must be weighed after qualifying and all cars that have completed two thirds of race distance must be weighed after each race, unless otherwise stated by the Clerk of the Course. Cars need to proceed to Parc Fermé directly after being weighed, unless otherwise stated by the Clerk of the Course.
- 15.18.3. The technical committee can at any time adjust the weights to keep competition fair.
- 15.18.4. Where the scales being used to weigh race cars at a circuit have been assessed as required by the regulations, they shall be deemed correct at the discretion of the Technical Committee (or its nominated representative/s).
- 15.18.5. Location of ballast is free of restriction within the cabin area or boot of the vehicle.
- 15.18.6. Vehicles may not be lightened by the removal of exterior bodywork.
- 15.18.7. The ballast weights will be bolted in to strengthening bars or plates that run across the floor that are welded or affixed to the roll cage or car's integral structure.
- 15.18.8. The weights in the wheel well can be secured as mentioned above or using a bar that is affixed to the roll cage bar running above the wheel well.
- 15.18.9. The bolts used to secure the weights must be minimum 20mm diameter using at least 5mm thick washers that are at least 100mm in diameter.
- 15.18.10. Attachments must be approved by the VW Challenge Technical Committee or MSA scrutineers.
- 15.18.11. Minimum weight: 1075kg
- 15.18.12. Battery may be moved to the boot wheel-well area, but must then be secured in a technically approved battery box.

16. CLASS B

16.1. PISTONS AND RINGS

- 16.1.1. Only single squish pad pistons may be used
- 16.1.2. 0.5mm maximum oversize pistons are allowed. 82.5mm standard
- 16.1.3. Minimum piston weight with rings and gudgeon pin is 370grams.
- 16.1.4. The pistons may be lightened by removing metal from the underside of the piston At least one piston must remain unmodified.
- 16.1.5. Original spec Nüral, Mahle pistons part number RPT83042 and Kombi pistons part number - Goldwagen: A843, Midas/Alert/general outlets: RP83045 and RP83052 may be used.

16.2. CONNECTING RODS

- 16.2.1. Only Standard OE VW Conrods are to be used.
- 16.2.2. Short Block: Conrods may be lightened and balanced. Minimum weight 550 grams includes bolts and nuts, excludes bearing shells.
- 16.2.3. Long Block: Conrods may be lightened and balanced. Minimum weight 580 grams includes bolts and nuts, excludes bearing shells.

16.3. CRANKSHAFTS

- 16.3.1. Stroking is not allowed.
- 16.3.2. May be balanced and reground.
- 16.3.3. Lightening is allowed by drilling and grinding.
- 16.3.4. Knife edging of webs is not allowed.
- 16.3.5. Side edging thickness of Web must remain standard (casting marks must remain visible).
- 16.3.6. Min weight: 13.5 kg no tolerance.

- 16.3.7. Only 2000cc crankshaft (92.8 mm stroke).
- 16.4. **FLYWHEEL AND CLUTCH**
- 16.4.1. Clutch plates are free of restriction.
- 16.4.2. May be lightened and balanced.
- 16.4.3. Min weight: Flywheel & pressure plate, excluding pressure plate to flywheel bolts: 7.2 Kg.
- 16.5. **INDUCTION SYSTEMS**
- 16.5.1. Additional air pipes may be used to supply the engine air intake with cool air.
- 16.5.2. Filters are free of restriction.
- 16.5.3. Throttle bodies may be modified to take alternate throttle position sensors.
- 16.5.4. MP9 or 2E manifold and throttle body.
- 16.5.5. Inlet manifold may not be gas flowed other than matching the ports to the cylinder head up to 80mm. (NB: the inlet manifold only, not the cylinder head).
- 16.5.6. Throttle body must remain standard with the exception of a hole of up to 8mm to aid idling and may be modified to take separate throttle position sensors.
- 16.5.7. Standard Polo or Citi Life air filter housing must be used (upper and lower cones in the box may be removed). On a 6R Polo, the inlet hole in the air box can be closed and moved to a different position, but has to remain the same internal diameter.
- 16.5.8. The standard connecting pipe between the throttle body and air filter housing may be replaced with a non-standard air tight pipe with the same continuous diameter and not exceeding 350mm in length.
- 16.6. **CYLINDER HEADS**
- 16.6.1. Valves must remain standard except valve stems may be shortened or lengthened.
- 16.6.2. Only standard OE or exact replacement functional hydraulic followers may be used
- 16.6.3. Minimum valve stem diameter is 7mm.
- 16.6.4. Only standard Gemtec or 2E, AGG or ADY 8v hydraulic head – max 40 mm intake and 34 mm exhaust valves allowed. Zero tolerance.
- 16.6.5. No gas flowing allowed but only one chamber can be repaired.
- 16.6.6. Standard Gemtec, 2E, AGG or ADY OE valves and valve springs and retainers only. Three angle seats are allowed.
- 16.7. **COMPRESSION RATIO**
- 10.8:1 Maximum. No tolerance.
- 16.8. **CAMSHAFTS**
- 16.8.1. The rotary position of the camshaft to the crankshaft may be changed by using an adjustable vernier pulley.
- 16.8.2. Cam hydraulic duration will be measured with a Checking height of 0.07 mm.
- 16.8.3. Only 288-degree advertised duration (crank angle). Tolerance ± 1.0 degree
- 16.8.4. Max 11.7mm cam lift.
- 16.8.5. Lobe Separation 108 to 110 degrees. Tolerance ± 1.0 degree.
- 16.9. **GEARBOXES AND DIRTS**
- 16.9.1. Only genuine VW 5-speed manual shift gearboxes may be used, as available on local models.
- 16.9.2. No automatic gearshift gearboxes in any form allowed.
- 16.9.3. No limited slip differentials.
- 16.9.4. Short shift gear linkage allowed.
- 16.9.5. Ratios must be VW OE replacement parts.
- 16.9.6. Linkage bushings may be changed for a harder material.
- 16.9.7. Drive shaft lengths may be modified to prevent C.V. joint failure.
- 16.9.8. The inspection plate "green plate" on the side of the gearbox must be wire locked.
- 16.9.9. Syncro rings may be removed
- 16.9.10. Only 3.94 diff ratio allowed
- 16.9.11. Only the following gear ratios are allowed:
- | | |
|-------------|----------------|
| First Gear | 3.455 |
| Second Gear | 1.944 or 2.120 |
| Third Gear | 1.444 |
| Fourth Gear | 1.129 |
| Fifth Gear | 0.894 or 0.912 |

16.10. MANAGEMENT SYSTEMS

Only original MP9, or SA manufactured systems that are freely commercially available (Dastek Unichip, Dictator, Perfect Power, Mr. Turbo, Gotech). Should a competitor want to use a locally produced management system not listed, they need to apply to the technical committee.

16.11. IGNITION SYSTEMS

16.11.1. Individual coils per cylinder are not allowed.

16.11.2. May run Wasted Spark Coil Pack.

16.12. FUEL INJECTION

16.12.1. Plastic injector rails may be used.

16.12.2. Fuel pressure regulators are free of restriction.

16.12.3. More than one fuel pump is allowed.

16.12.4. Fuel pumps are free of restriction.

16.12.5. Exterior additional fuel surge tanks are allowed but must comply with the fuel regulations in the GCR's. The competitor must take full responsibility of the installation.

16.12.6. Fuel radiators/coolers or cooling of fuel in any way is not allowed.

16.12.7. Only original spec injectors may be used, part no: 037906031AA or Digifant injector rails, part no: 037133313J may be used.

16.13. EXHAUST SYSTEMS

16.13.1. Exhaust systems are free of restriction.

16.13.2. Must comply with GCR 245 and must exit at the rear of the car in the original position and direction.

16.13.3. The exhaust outlet pipe may not be recessed towards the inside of the bodywork of the vehicle, i.e. recessed further than the bottom part of the bodywork or bumper/spoiler where the exhaust protrudes.

16.13.4. The exhaust must also not protrude beyond the perimeter of the vehicle.

16.13.5. The exhaust must follow the original route of the standard OE exhaust system.

16.14. SUSPENSION

16.14.1. Top shock turrets must remain in standard position except for modifications in terms of 16.14.21.

16.14.2. Standard VW OE steering rack and standard mounting positions only, power steering may be disconnected. If power steering is used it must be a standard VW part.

16.14.3. Bush material is free however must be dimensionally identical to standard items.

16.14.4. Pick-up points on body / chassis may not be changed or moved.

16.14.5. Steering knuckles must be a standard VW OE part and match the specific model of that vehicle.

16.14.6. Golf II, III, IV, P1, P2 and P3 may use a rose joint in replacement of the rear control arm bush, but must be in the standard position.

16.14.7. Shocks / uprights may be slotted to achieve camber settings only.

16.14.8. Ball joints and their mountings may not be slotted. For camber purposes only P2, P3, Golf 4, Golf 5, Golf 6 and Beetle may be fitted with ball joint adaptor plates allowing a maximum additional extension per side of 25mm. These adaptor plates may not be used to alter the lower control arm angle in any way. P2 Polos are allowed to use P3 control arms. The maximum track width must still be adhered to.

16.14.9. Top and bottom stress bars are allowed.

16.14.10. Steering rack mounting on MK1 Golf/Jetta/Fox must be reinforced.

16.14.11. Mk1 Golf/Jetta/Fox knuckle may be machined to accommodate 39 and 40 mm hubs and bearings for safety reason only.

16.14.12. Mk1/2/3 Golf/Jetta/Fox may use new Polo/Golf 4 type rear stub axle with pressed wheel-bearing, for safety reasons, with modifications to allow the fitment of the currently used brake calipers.

16.14.13. Droop may be limited.

16.14.14. Hubs of 4 or 5 stud type specification are allowed in all classes.

16.14.15. Camber/Caster plates with a maximum caster offset of 40 mm are allowed and may be fitted on top or directly below the turret.

16.14.16. Ackerman angle may be altered.

16.14.17. Anti-roll bar material and thickness may be changed. Rear anti-roll bar must fit directly onto rear axle and must follow the contour of the rear axle. The roll bar may not be fitted remotely in its working principle.

- 16.14.18. Rear axle may be stiffened by fitting fixed stiffeners along the straight edge of the axle only. Rear axle control arms may be strengthened by welding in a gusset plate of maximum 5mm thickness.
- 16.14.19. Shock makes Bilstein, Koni, Gabriel, Monroe, Sachs, Wietec, Armstrong, Spax, Leda, Sax, KW, Traxion or Ian Glass coil over type shocks are allowed.
- 16.14.20. Short rear shock absorbers may be accommodated by adding brackets to top and / or bottom mounting positions.
- 16.14.21. To accommodate long front absorbers front strut tower may be lengthened but 40mm castor offset must still be adhered to.
- 16.14.22. External gas canisters not allowed.
- 16.14.23. Spacer / mounting plate may be fitted between stub axle and rear axle assembly to allow for caliper to be shimmed with stub axle.
- 16.15. **BRAKES**
- 16.15.1. Boosters may be removed, but standard VW master cylinder must be retained.
- 16.15.2. Discs may be slotted and/or cross-drilled.
- 16.15.3. Rear brakes can be drums or discs.
- 16.15.4. Friction material is free.
- 16.15.5. Brake balance adjustment is allowed in car within reach of driver.
- 16.15.6. Standard VW single piston floating calipers with aftermarket brake pads and discs up to a maximum of 288mm diameter.
- 16.16. **WHEELS AND TYRES**
- 16.16.1. No chrome plated or split rims are allowed. Rim size 15 inch, 7J max.
- 16.16.2. Tyres are DUNLOP DZ03G H1 compound 195/55-R15, or as approved by the Technical Committee.
- 16.16.3. The VW Challenge Committee has the authority to appoint an official tyre marker at a race meeting.
- 16.16.4. At any given race meeting, four tyres will be positively identified by the technical committee or scrutineer prior to the start of qualifying and these tyres must be used for the remainder of the race meeting.
- 16.16.5. It is the responsibility of the competitor to ensure their tyres are marked by the official tyre marker before official timed practice.
- 16.16.6. It is the responsibility of the competitor to ensure that the tyre markings remain on the tyre, as the use of unmarked tyres during the meeting, inclusive of qualifying, can result in the exclusion of the competitor concerned.
- 16.16.7. The only time four new i.e. unmarked tyres may be used is at a competitor's first race of a new race season.
- 16.16.8. At the discretion of the technical consultant/scrutineer a damaged or defective tyre may be replaced during a race meeting with a tyre of similar wear.
- 16.16.9. In the event of a competitor replacing/building a new car they must transfer their current tyres to their new car.
- 16.16.10. Pressure controlling "pop-off" valves may not be used.
- 16.16.11. Two new tyres will be allowed every race meeting
- 16.17. **SPECIFICATION SHEET**
- Chassis specifications and general measurements are available from the Technical Committee. All specifications are subject to 0.5 % tolerance except where no tolerance is allowed. (P1 refers to old 6K old Polo Classic and Playa, P2 refers to 9N Polo and Vivo, P3 refers to new 6R Polo)
- 16.17.1. Ground Clearance:
- 125 mm minimum
 - Note: The measurements above are taken with the driver in the car from the centre of the bolt on the front inner lower control arm (standard mounting point) to the ground.
- 16.17.2. Front Track Width:
- This measurement will be taken at the bottom of the wheel (closest to the ground) from the outer edge of the wheel (rim) bead face.
 - The widest part of the two opposing wheel rims, no tolerance:
 - Mk1: 1680mm
 - Mk2 & P1: 1710mm
 - Mk3: 1730mm
 - Mk4, Mk5, Mk6, Beetle, P2 & P3: 1740mm

16.17.3. Wheel Base

- The wheel base of a car may not be increased from the standard wheel base. Wheel base is measured from back of rear rim to back of front rim. The wheel base on the various models shall not exceed:
 - Golf Mk1 wheel base 2410mm (plus 5mm) maximum
 - Golf Mk2 wheel base 2471mm (plus 5mm) maximum
 - Golf Mk3 wheel base 2475mm (plus 5mm) maximum
 - Golf Mk4 wheel base 2511mm (plus 5mm) maximum
 - Polo P1 (6K) wheel base 2440mm (plus 5mm) maximum
 - Polo P2 (9N) wheel base 2460mm (plus 5mm) maximum
 - Polo P3 (6R) wheel base 2470mm (plus 5mm) maximum
 - Beetle wheel base 2508mm (plus 5mm) maximum
- Front control arms may not be pushed or spaced forward in any way. Sub frame may also not be slotted and standard diameter mounting bolts must be used.
- Rear axle mounting points may not be slotted or modified to allow wheel base to be lengthened or shortened.

16.18. CAR MASS (Including driver)

- 16.18.1. The vehicle mass is as car is raced. At no time of the event may a car weigh less than stipulated. No tolerance.
- 16.18.2. All cars must be weighed after qualifying and all cars that have completed two thirds of race distance must be weighed after each race, unless otherwise stated by the Clerk of the Course. Cars need to proceed to Parc Fermé directly after being weighed unless otherwise stated by the Clerk of the Course.
- 16.18.3. The technical committee can at any time adjust the weights to keep competition fair.
- 16.18.4. Where the scales being used to weigh race cars at a circuit have been assessed as required by the regulations, they shall be deemed correct at the discretion of the Technical Committee (or its nominated representative/s).
- 16.18.5. Location of ballast is free of restriction within the cabin area or boot of the vehicle.
- 16.18.6. Vehicles may not be lightened by the removal of exterior bodywork.
- 16.18.7. The ballast weights will be bolted in to strengthening bars or plates that run across the floor that are welded or affixed to the roll cage or car's integral structure.
- 16.18.8. The weights in the wheel well can be secured as mentioned above or using a bar that is affixed to the roll cage bar running above the wheel well.
- 16.18.9. The bolts used to secure the weights must be minimum 20mm diameter using at least 5mm thick washers that are at least 100mm in diameter.
- 16.18.10. Attachments must be approved by the VW Challenge Technical Committee or MSA scrutineers.
- 16.18.11. Minimum weight: 1050 kg.

17. CLASS C

17.1. PISTONS AND RINGS

- 17.1.1. Only single squish pad pistons may be used.
- 17.1.2. Oversize pistons are not allowed. 82.5mm
- 17.1.3. Minimum piston weight with rings and gudgeon pin is 370 grams. The piston lightened by removing metal from the underside of the piston. At least one piston must remain unmodified.
- 17.1.4. Only original spec or replacement part Nüral, Mahle part number RPT83042 pistons may be used.

17.2. CONNECTING RODS

- 17.2.1. Only Standard OE VW Conrods are to be used.
- 17.2.2. Conrods may be lightened and balanced. Minimum weight: 580 grams includes bolts and nuts, excludes bearing shells.

17.3. CRANKSHAFTS

- 17.3.1. Stroking is not allowed.
- 17.3.2. May be balanced and reground.
- 17.3.3. Lightening is allowed by drilling and grinding.

- 17.3.4. Knife edging of webs is not allowed.
- 17.3.5. Side edging thickness of Web must remain standard (casting marks must remain visible).
- 17.3.6. Min weight: 13.5 kg no tolerance.
- 17.3.7. Only 2000cc crankshaft (92.8 mm stroke)
- 17.4. **FLYWHEEL AND CLUTCH**
 - 17.4.1. Clutch plates are free of restriction.
 - 17.4.2. May be lightened and balanced.
 - 17.4.3. Min weight: Flywheel & pressure plate, excluding pressure plate to flywheel bolts: 7.2 Kg.
- 17.5. **INDUCTION SYSTEMS**
 - 17.5.1. Additional air pipes may be used to supply the engine air intake with cool air.
 - 17.5.2. Filters are free of restriction.
 - 17.5.3. Throttle bodies may be modified to take alternate throttle position sensors.
 - 17.5.4. Only 2E (Part No 037133223K) intake manifold and throttle body allowed.
 - 17.5.5. Inlet manifold may not be gas flowed other than matching the ports to the cylinder head up to 10mm or coated in any way (NB: the inlet manifold only, not the cylinder head).
 - 17.5.6. Throttle body must remain standard with the exception of a hole of up to 8mm to aid idling and may be modified to take separate throttle position sensors. Maximum butterfly size 56mm
 - 17.5.7. Standard Polo or Citi Life air filter housing must be used (upper and lower cones in the box may be removed). On a 6R Polo, the inlet hole in the air box can be closed and moved to a different position, but has to remain the same internal diameter.
 - 17.5.8. The standard connecting pipe between the throttle body and air filter housing may be replaced with a non-standard air tight pipe with the same continuous diameter and not exceeding 350mm in length.
- 17.6. **CYLINDER HEADS**
 - 17.6.1. Valves must remain standard except valve stems may be shortened or lengthened.
 - 17.6.2. Only standard OE or exact replacement functional hydraulic followers may be used
 - 17.6.3. Minimum valve stem diameter is 7mm.
 - 17.6.4. Only standard 2E, AGG or ADY OE 8v hydraulic head – max 40 mm intake and 34 mm exhaust valves allowed. Zero tolerance.
 - 17.6.5. Standard 2E, AGG or ADY OE valves and valve springs and retainers only.
 - 17.6.6. No gas flowing allowed but only one chamber can be repaired.
 - 17.6.7. Three angle seats are allowed.
 - 17.6.8. Minimum combustion cc is 29.0cc.
- 17.7. **COMPRESSION RATIO**
 - 17.7.1. 10.2:1 maximum. No tolerance
- 17.8. **CAMSHAFTS**
 - 17.8.1. The rotary position of the camshaft to the crankshaft may be changed by using an adjustable vernier pulley.
 - 17.8.2. Cam hydraulic duration will be measured with a Checking height of 0.07 mm.
 - 17.8.3. Only 288-degree advertised duration (crank angle). Tolerance ± 1.0 degree
 - 17.8.4. Max 11.7mm lift.
 - 17.8.5. Lobe Separation 108 to 110 degrees. Tolerance ± 1.0 degree.
- 17.9. **GEARBOXES AND DIFFS**
 - 17.9.1. Only genuine VW 5-speed manual shift gearboxes may be used, as available on local models.
 - 17.9.2. No automatic gearshift gearboxes in any form allowed.
 - 17.9.3. No limited slip differentials.
 - 17.9.4. Short shift gear linkage allowed.
 - 17.9.5. Ratios must be VW OE replacement parts.
 - 17.9.6. Linkage bushings may be changed for a harder material.
 - 17.9.7. Drive shaft lengths may be modified to prevent C.V. joint failure.
 - 17.9.8. The inspection plate “green plate” on the side of the gearbox must be wire locked.
 - 17.9.9. Syncro rings may be removed
 - 17.9.10. Only 3.94 diff ratio allowed
 - 17.9.11. Only the following gear ratios are allowed:

First Gear	3.455
Second Gear	1.944 or 2.120
Third Gear	1.444

Fourth Gear	1.129
Fifth Gear	0.894 or 0.912

17.10. **MANAGEMENT SYSTEMS**

Only SA manufactured systems that are freely commercially available (Dicktator, Perfect Power, Mr. Turbo, Gotech). Should a competitor want to use a locally produced management system not listed, they need to apply to the technical committee.

17.11. **IGNITION SYSTEMS**

- 17.11.1. Individual coils per cylinder are not allowed.
- 17.11.2. Wasted Spark Coil Pack is not allowed.
- 17.11.3. Standard OE operational distributor must be actively used.

17.12. **FUEL INJECTION**

- 17.12.1. Plastic injector rails may be used.
- 17.12.2. Fuel pressure regulators are free of restriction.
- 17.12.3. More than one fuel pump is allowed.
- 17.12.4. Fuel pumps are free of restriction.
- 17.12.5. Exterior additional fuel surge tanks are allowed but must comply with the fuel regulations in the GCR's. The competitor must take full responsibility of the installation.
- 17.12.6. Fuel radiators/coolers or cooling of fuel in any way is not allowed.
- 17.12.7. Original spec injectors, part no: 037906031AA or Digifant injector rails, part no: 037133313J may be used.

17.13. **EXHAUST SYSTEMS**

- 17.13.1. Must comply with GCR 245 and must exit at the rear of the car in the original position and direction.
- 17.13.2. The exhaust outlet pipe may not be recessed towards the inside of the bodywork of the vehicle, i.e. recessed further than the bottom part of the bodywork or bumper/spoiler where the exhaust protrudes.
- 17.13.3. The exhaust must also not protrude beyond the perimeter of the vehicle.
- 17.13.4. The exhaust must follow the original route of the standard OE exhaust system.
- 17.13.5. Only the standard 2E OE exhaust manifold, part No 027253033BC or 037253033E.
- 17.13.6. Other than machining and matching the exhaust manifold to the cylinder head up to 10mm into the exhaust manifold (NB: the exhaust manifold only, not the cylinder head) the exhaust manifold may not be flowed and may not be coated in any way.
- 17.13.7. The downpipe from the exhaust manifold to the knuckle must have an OD of maximum 45mm at all points and may not be longer than 1000 mm in length and may have no additional internal fitted parts. The rest of the exhaust may only be a single pipe that must follow the original route of the standard exhaust system and must exit at the rear of the car in the original position and may not be larger at any point than 57mm OD, except for the silencer.
- 17.13.8. The silencer must be placed behind the rear axle and must also have an inlet and outlet OD of maximum 57mm and may have no internal megaphone shaped parts. The tailpipe after the maximum 57mm outlet to the silencer is free.

17.14. **SUSPENSION**

- 17.14.1. Top shock turrets must remain in standard position except for modifications in terms of 17.14.23.
- 17.14.2. Standard VW OE steering rack and standard mounting positions only, power steering may be disconnected. If power steering is used it must be a standard VW part.
- 17.14.3. Bush material is free however must be dimensionally identical to standard items.
- 17.14.4. Pick-up points on body / chassis may not be changed or moved.
- 17.14.5. Steering knuckles must be a standard VW OE part and match the specific model of that vehicle.
- 17.14.6. Golf II, III, IV, P1, P2 and P3 may use a rose joint in replacement of the rear control arm bush, but must be in the standard position.
- 17.14.7. Shocks / uprights may be slotted to achieve camber settings only.
- 17.14.8. Ball joints and their mountings may not be slotted. For camber purposes only P2, P3, Golf 4, Golf 5, Golf 6 and Beetle may be fitted with ball joint adaptor plates allowing a maximum additional extension per side of 25mm. These adaptor plates may not be used to alter the lower control arm angle in any way. P2 Polos are allowed to use P3 control arms. The maximum track width must still be adhered to.

- 17.14.9. Top and bottom stress bars are allowed.
- 17.14.10. Steering rack mounting on MK1 Golf/Jetta/Fox must be reinforced.
- 17.14.11. Mk1 Golf/Jetta/Fox knuckle may be machined to accommodate 39 and 40 mm hubs and bearings for safety reason only.
- 17.14.12. Mk1/2/3 Golf/Jetta/Fox may use new Polo/Golf 4 type rear stub axle with pressed wheel-bearing, for safety reasons, with modifications to allow the fitment of the currently used brake calipers.
- 17.14.13. Droop may be limited.
- 17.14.14. Hubs of 4 or 5 stud type specification are allowed in all classes.
- 17.14.15. Ackerman angle may not be altered.
- 17.14.16. Anti-roll bar material and thickness may be changed. Rear anti-roll bar must fit directly onto rear axle and must follow the contour of the rear axle. The roll bar may not be fitted remotely in its working principle.
- 17.14.17. Rear axle may be stiffened by fitting fixed stiffeners along the straight edge of the axle. Rear axle control arms may be strengthened by welding in a gusset plate of maximum 5mm thickness.
- 17.14.18. Camber/Caster plates with a maximum caster offset of 40 mm are allowed and may be fitted on top or directly below the turret.
- 17.14.19. Ackerman angle may not be altered.
- 17.14.20. Only one spring per shock allowed, no helper springs
- 17.14.21. Shock absorbers allowed:
 - Ian Glass supplied, non-adjustable, locally manufactured, non-gas assisted, large OE coil type, sealed, GT shocks utilizing springs that fit into the original OE seating points or coil-over springs where the ride height is adjustable by using spacers and or threaded outer casing.
 - Non gas assisted Koni coil-over type shocks. Part No Front: 8610-1436-RACE, Part No Rear: 8041-1101-SPORT,
 - Locally assembled, gas assisted Bilstein coil-over type shocks.
 - Maxtrac Coil Overs Series 3.03/3.04
 - KW shocks formerly used in national VW Polo Cup part number front 1J0972329E.
 Any Class C competitor's Shock absorber information / specifications will be available to all Class C competitors.
- 17.14.22. Short rear shock absorbers may be accommodated by adding brackets to top and / or bottom mounting positions.
- 17.14.23. To accommodate long front absorbers front strut tower may be lengthened but 40mm castor offset must still be adhered to.
- 17.14.24. External gas canisters not allowed.
- 17.14.25. Spacer / mounting plate may be fitted between stub axle and rear axle assembly to allow for caliper to be shimmed with stub axle.

17.15. BRAKES

- 17.15.1. Boosters may be removed, but standard VW master cylinder must be retained.
- 17.15.2. Discs may be slotted and/or cross-drilled.
- 17.15.3. Rear brakes can be drums or discs.
- 17.15.4. Friction material is free.
- 17.15.5. Brake balance adjustment is allowed in car within reach of driver.
- 17.15.6. Standard VW single piston floating calipers with aftermarket brake pads and discs up to a maximum of 288mm diameter.
- 17.15.7. Standard OE adjustable brake compensating load valve is allowed.

17.16. WHEELS AND TYRES

- 17.16.1. No chrome plated or split rims are allowed. Rim size 15 inch, 7J max.
- 17.16.2. Tyres are Bridgestone Potenza Adrenalin RE002 195/50-R15, or as approved by the Technical Committee.
- 17.16.3. Tyres may not be skimmed.
- 17.16.4. The VW Challenge Committee has the authority to appoint an official tyre marker at a race meeting.

- 17.16.5. At any given race meeting, four tyres will be positively identified by the technical committee or scrutineer prior to the start of qualifying and these tyres must be used for the remainder of the race meeting.
- 17.16.6. It is the responsibility of the competitor to ensure their tyres are marked by the official tyre marker before official timed practice.
- 17.16.7. It is the responsibility of the competitor to ensure that the tyre markings remain on the tyre, as the use of unmarked tyres during the meeting, inclusive of qualifying, can result in the exclusion of the competitor concerned.
- 17.16.8. The only time four new i.e. unmarked tyres may be used is at a competitor's first race of a new race season.
- 17.16.9. At the discretion of the technical consultant/scrutineer a damaged or defective tyre may be replaced during a race meeting with a tyre of similar wear.
- 17.16.10. In the event of a competitor replacing/building a new car they must transfer their current tyres to their new car.
- 17.16.11. Pressure controlling "pop-off" valves may not be used.
- 17.16.12. One new tyre will be credited to the competitor at every race meeting. The competitor may choose to use to tyre at that race meeting or bank it for a future race. No more than one tyre can be banked at any stage.

17.17. **SPECIFICATION SHEET**

Chassis specifications and general measurements are available from the Technical Committee. All specifications are subject to 0.5 % tolerance except where no tolerance is allowed. (P1 refers to old 6K old Polo Classic and Playa, P2 refers to 9N Polo and Vivo, P3 refers to new 6R Polo)

17.17.1. Ground Clearance:

- 130 mm minimum

17.17.2. Note: The measurements above are taken with the driver in the car from the centre of the bolt on the front inner lower control arm (standard mounting point) to the ground. Front Track Width:

- This measurement will be taken at the bottom of the wheel (closest to the ground) from the outer edge of the wheel (rim) bead face.
- The widest part of the two opposing wheel rims, no tolerance:
 - Mk1: 1670mm
 - Mk2 & P1: 1710mm
 - Mk3, P2 & P3: 1730mm
 - Mk4, Mk5, Mk6 & Beetle: 1740mm

17.17.3. Wheel Base

- The wheel base of a car may not be increased from the standard wheel base. Wheel base is measured from back of rear rim to back of front rim. The wheel base on the various models shall not exceed:
 - Golf Mk1 wheel base 2410mm (plus 5mm) maximum
 - Golf Mk2 wheel base 2471mm (plus 5mm) maximum
 - Golf Mk3 wheel base 2475mm (plus 5mm) maximum
 - Golf Mk4 wheel base 2511mm (plus 5mm) maximum
 - Polo P1 (6K) wheel base 2440mm (plus 5mm) maximum
 - Polo P2 (9N) wheel base 2460mm (plus 5mm) maximum
 - Polo P3 (6R) wheel base 2470mm (plus 5mm) maximum
 - Beetle wheel base 2508mm (plus 5mm) maximum
- Front control arms may not be pushed or spaced forward in any way. Sub frame may also not be slotted and standard diameter mounting bolts must be used.
- Rear axle mounting points may not be slotted or modified to allow wheel base to be lengthened or shortened.

17.18. **CAR MASS (Including driver)**

- 17.18.1. The vehicle mass is as car is raced. At no time of the event may a car weigh less than stipulated. No tolerance.
- 17.18.2. All cars must be weighed after qualifying and all cars that have completed two thirds of race distance must be weighed after each race, unless otherwise stated by the Clerk of the Course. Cars need to proceed to Parc Fermé directly after being weighed, unless otherwise stated by the Clerk of the Course.

- 17.18.3. The technical committee can at any time adjust the weights to keep competition fair.
- 17.18.4. Where the scales being used to weigh race cars at a circuit have been assessed as required by the regulations, they shall be deemed correct at the discretion of the Technical Committee (or its nominated representative/s).
- 17.18.5. Location of ballast is free of restriction within the cabin area or boot of the vehicle.
- 17.18.6. Vehicles may not be lightened by the removal of exterior bodywork.
- 17.18.7. The ballast weights will be bolted in to strengthening bars or plates that run across the floor that are welded or affixed to the roll cage or car's integral structure.
- 17.18.8. The weights in the wheel well can be secured as mentioned above or using a bar that is affixed to the roll cage bar running above the wheel well.
- 17.18.9. The bolts used to secure the weights must be minimum 20mm diameter using at least 5mm thick washers that are at least 100mm in diameter.
- 17.18.10. Attachments must be approved by the VW Challenge Technical Committee or MSA scrutineers.
- 17.18.11. Minimum weight: 1050kg.